



# GROVE®

## FULL HYDRAULIC CARRIER-MOUNTED CRANE

# TMS 375LP

## 45 TON CAP.

PCSA CLASS 10-157

### RATED LIFTING CAPACITIES 35 ft. - 121 ft. BOOM WITH FULLY EXTENDED OUTRIGGERS

#### ON OUTRIGGERS OVER SIDE

Radius in Feet	Trapezoidal Boom Length in Feet					89 + 32 Ext.
	*35	49	62	76	89	121
10	90,000					
12	80,000	56,000				
15	69,000	54,400	48,000			
20	53,000	49,800	44,300	35,000		
25	38,600	38,600	38,600	34,200	24,700	
30	25,900	25,900	25,900	25,900	23,700	17,500
35		19,500	19,500	19,500	19,500	15,000
40		15,700	15,700	15,700	15,700	13,000
45		12,500	12,500	12,500	12,500	11,550
50			10,100	10,100	10,100	10,400
55			8,300	8,300	8,300	9,400
60			6,800	6,800	6,800	8,060
65				5,600	5,600	6,780
70				4,600	4,600	5,700
75					3,750	4,800
80					3,000	4,050
85					2,400	3,425
90						2,850
95						2,350
100						1,900
105						1,500
110						1,150
115						850

**32 ft. Ext. Capacities	
Boom Angle	Capacity
76°	17,500
74°	15,000
72°	13,000
69°	11,550
67°	10,400
64°	9,400
61°	8,600
59°	7,900
56°	7,300
53°	6,800
49°	6,300
46°	5,900
42°	5,600
39°	5,300
34°	5,000
29°	4,700
24°	4,500
15°	4,300

Radius in Feet	60 ft. JIB CAPACITIES	
	No Offset	7½° Offset
10		
12		
15		
20		
25		
30		
35		
40	76.0°	11,000
45	74.0°	9,700
50	72.0°	8,300
55	70.5°	7,450
60	68.0°	6,550
65	66.5°	5,800
70	64.0°	5,300
75	62.0°	4,800
80	59.5°	4,050
85	57.5°	3,425
90	55.0°	2,850
95	52.5°	2,350
100	49.5°	1,900
105	47.0°	1,500
110	44.0°	1,150
115	40.5°	850

#### ON OUTRIGGERS OVER REAR

Radius in Feet	Trapezoidal Boom Length in Feet					89 + 32 Ext.
	*35	49	62	76	89	121
10	90,000					
12	80,000	56,000				
15	69,000	54,400	48,000			
20	53,000	49,800	44,300	35,000		
25	40,500	40,500	39,200	34,200	24,700	
30	27,100	27,100	27,100	27,100	23,700	17,500
35		20,500	20,500	20,500	20,500	15,000
40		17,000	17,000	17,000	17,000	13,000
45		13,800	13,800	13,800	13,800	11,550
50			11,400	11,400	11,400	10,400
55			9,550	9,550	9,550	9,400
60			8,000	8,000	8,000	8,600
65				6,800	6,800	7,600
70				5,750	5,750	6,500
75					4,850	5,600
80					4,000	4,800
85					3,400	4,150
90						3,550
95						3,050
100						2,550
105						2,150
110						1,800
115						1,450

**32 ft. Ext. Capacities	
Boom Angle	Capacity
76°	17,500
74°	15,000
72°	13,000
69°	11,550
67°	10,400
64°	9,400
61°	8,600
59°	7,900
56°	7,300
53°	6,800
49°	6,300
46°	5,900
42°	5,600
39°	5,300
34°	5,000
29°	4,700
24°	4,500
15°	4,300

Radius in Feet	60 ft. JIB CAPACITIES	
	No Offset	7½° Offset
10		
12		
15		
20		
25		
30		
35		
40	76.0°	11,000
45	74.0°	9,700
50	72.0°	8,300
55	70.5°	7,450
60	68.0°	6,550
65	66.5°	5,800
70	64.0°	5,300
75	62.0°	4,800
80	59.5°	4,050
85	57.5°	3,425
90	55.0°	2,850
95	52.5°	2,350
100	49.5°	1,900
105	47.0°	1,500
110	44.0°	1,150
115	40.5°	850

#### TRAPEZOIDAL BOOM and 32 FT. EXTENSION NOTES

Capacities appearing in shaded area are based upon structural strength and tipping should not be relied upon as a capacity limitation. Capacities are in pounds and do not exceed 85% of tipping loads with counterweight fully extended.

\*Capacities in shaded area for 35 ft. boom length shall be lifted with boom fully retracted. If boom is not fully retracted, capacities shall not exceed those shown for 49 ft. boom length.

\*\*These capacities are based on structural strength of 32 ft. ext. at listed boom angle regardless of boom length. When lifting with 32 ft. ext. and LESS THAN a fully extended trapezoidal boom, the loads lifted MUST NOT EXCEED the 32 ft. ext. structural capacity at the listed boom angle OR the largest stability capacity listed for the actual working radius, whichever is less.

#### 60 FT. JIB NOTES

Capacities appearing in shaded area are based on structural strength of the jib.

Capacities below the shaded area are based on stability and do not exceed 85% of tipping loads with counterweight fully extended.

Rated load is based on main boom angle regardless of main boom length. Radius in Feet column applies to jib capacities only with main boom fully extended.

Maximum length of main boom for purposes of erecting 60 ft. jib is 62 ft.

**WARNING:** Operation of the machine with heavier loads than the capacities listed is strictly prohibited. Machine tipping with 60 ft. jib occurs rapidly and without advance notice.

For main boom length greater than 62 ft. with 60 ft. jib in working position, the main boom angle must not be below 37° since loss of stability will occur causing a tipping condition.